



*DC COMPONENTS CO., LTD.*

RECTIFIER SPECIALISTS

DB151  
THRU  
DB157

**TECHNICAL SPECIFICATIONS OF SINGLE-PHASE SILICON BRIDGE RECTIFIER**

**VOLTAGE RANGE - 50 to 1000 Volts**

**CURRENT - 1.5 Amperes**

**FEATURES**

- \* Good for automation insertion
- \* Surge overload rating - 50 Amperes peak
- \* Ideal for printed circuit board
- \* Reliable low cost construction
- \* Glass passivated junction

**MECHANICAL DATA**



- \* Case: Molded plastic
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Lead: MIL-STD-202E, Method 208 guaranteed
- \* Polarity: Symbols molded or marked on body
- \* Mounting position: Any
- \* Weight: 0.4 gram

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified.  
Single phase, half wave, 60 Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.



DB-1



Dimensions in inches and (millimeters)

|   | SYMBOL           | DB151        | DB152 | DB153 | DB154 | DB155 | DB156 | DB157 | UNITS              |
|---|------------------|--------------|-------|-------|-------|-------|-------|-------|--------------------|
| Maximum Recurrent Peak Reverse Voltage  | VRRM             | 50           | 100   | 200   | 400   | 600   | 800   | 1000  | Volts              |
| Maximum RMS Bridge Input Voltage  | VRMS             | 35           | 70    | 140   | 280   | 420   | 560   | 700   | Volts              |
| Maximum DC Blocking Voltage   | Vdc              | 50           | 100   | 200   | 400   | 600   | 800   | 1000  | Volts              |
| Maximum Average Forward Output Current at TA = 40°C   | Io               | 1.5          |       |       |       |       |       |       | Amps               |
| Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method) | IFSM             | 50           |       |       |       |       |       |       | Amps               |
| Maximum Forward Voltage Drop per element at 1.5A DC   | VF               | 1.1          |       |       |       |       |       |       | Volts              |
| Maximum DC Reverse Current at Rated DC Blocking Voltage per element                               | @TA = 25°C       | 10           |       |       |       |       |       |       | uAmps              |
|   | @TA = 125°C      | 500          |       |       |       |       |       |       |                    |
| I <sup>2</sup> t Rating for Fusing (t<8.3ms)  | I <sup>2</sup> t | 10.4         |       |       |       |       |       |       | A <sup>2</sup> Sec |
| Typical Junction Capacitance ( Note1)   | CJ               | 25           |       |       |       |       |       |       | pF                 |
| Typical Thermal Resistance (Note 2)   | RθJA             | 40           |       |       |       |       |       |       | °C/W               |
| Operating and Storage Temperature Range   | TJ,TSTG          | -55 to + 150 |       |       |       |       |       |       | °C                 |

NOTES : 1.Measured at 1 MHz and applied reverse voltage of 4.0 volts

2.Thermal Resistance from Junction to Ambient and from junction to lead mounted on P.C.B. with 0.5 x 0.5" (13x13mm) copper pads.

# RATING AND CHARACTERISTIC CURVES ( DB151 THRU DB157)

FIG. 1 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 2 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS





FIG. 4 - TYPICAL REVERSE CHARACTERISTICS



## Disclaimer

Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold *DC COMPONENTS* harmless against all damages.

*DC COMPONENTS* disclaims any and all liability arising out of the application or use of any product, including consequential or incidental damages. Statement regarding the suitability of products for certain types of applications are based on *DC COMPONENTS*'s knowledge of typical requirements that are often placed on *DC COMPONENTS* products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

*DC COMPONENTS* reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein, and disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. Parameters provided in datasheets and specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify *DC COMPONENTS*'s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Unless otherwise in writing, *DC COMPONENTS* products are intended for use as general electronic components in standard applications ( eg: Consumer electronic, Computer equipment, Office equipment, etc.), and not recommended for use in a high specific application where a failure or malfunction of the device could result in human injury or death ( eg: Aerospace equipment, Submarine cables, Combustion equipment, Safety devices, Life support systems, etc.)

Customers using or selling *DC COMPONENTS* products not expressly indicated for use in such applications do so at their own risk. If customer intended to use *DC COMPONENTS* standard quality grade devices for applications not envisioned by *DC COMPONENTS*, please contact our sales representatives in advance.



*DC COMPONENTS CO., LTD.*